OFFICE OF THE MARION COUNTY SURVEYOR 5100 SECTION RECORD CORNER
SECTION 22 TOWNSHIP 14
DATE: 6-7-03 4-17-08 - RANGE __4 Ave PARTY CHIEF: __ Wilcoxen CREW: erson TYPE OF MARKER: Harrison METHOD OF ESTABLISHMENT: ____County: 10-24-98 Em IN. S.P.C. E ZONE NAD '83 NAME: 14042208 S. County Line Rd 9000 S N: 487249.5274(m) 65101.3191(m) E: 5. ш 5550 concrete median 0 S. County Line 9000 S Section 1.

Original post set 1820 by John Hendricks with witnesses: 28" ash S 58 W 6 links; 7" beech N 34 E 22 links per Marion County Atlas pg. 9. Percy Hosbrook 11-10-1849 called no stone but witness: (1) green and (1) stump of 20" ash N 77 E 23 links per Franklin Township Legal Survey Book pg. 26. GWS 10-10-63 called pipe by stone. McLand 1-28-69 called stone. McLand 5-11-71 called stone 3" down. Wilcoxen 8-20-75 called brass plug. Greene 7-11-87 called brass plug. Whiteside 4-3-96 called PK nail w/shiner over brass plug. Excavated by Wilcoxen 10-24-98 and set Harrison in accordance with 1-65 construction project. Re-tied 6-7-03 by Wilcoxen.

1	6								_	_	~	1		-	0	,,,								
																	1	4	0	4	2	2	0	18

		14042208
REF.	DISTANCE	DESCRIPTION
1.	89.66	Mag nail w/brass washer NE PwP#2-824 50"up
2.	140.56	Cut 'x' in SE bolt of highway sign I-65 north
3.	99.95	Cut 'x' in bolt of guard rail
4.	137.86	Due W to mag nail w/brass washer in joint of median
5.	47.92	Cut 'x' in bolt in guard rail